

Title: WIRELESS PERSONAL TRACKING
AND NAVIGATION SYSTEM
Inventors: STEPHEN O. BOZZONE
Client/Mtr: CE11234JI023 (9640/133)
Serial No.:
Filed:
Items Mailed: Patent Transmittal Letter (2); Patent Application with 3 sheets of drawings
and 23 sheets of specification (including title page); Combined Declaration and Power of
Attorney; Assignment Cover Sheet; Assignment; Information Disclosure Statement and
Form PTO-1449 and Postcard mailed on AUGUST 7, 2003.
EXPRESS MAIL LABEL NO. EV 318 174 036 US
Today's Date: AUGUST 7, 2003

EV318174036US

Title: WIRELESS PERSONAL TRACKING
AND NAVIGATION SYSTEM
Inventors: STEPHEN O. BOZZONE
Client/Mtr: CE11234JI023 (9640/133)
Serial No.:
Filed:
Items Mailed: Patent Transmittal Letter (2); Patent Application with 3 sheets of drawings
and 23 sheets of specification (including title page); Combined Declaration and Power of
Attorney; Assignment Cover Sheet; Assignment; Information Disclosure Statement and
Form PTO-1449 and Postcard mailed on AUGUST 7, 2003.
EXPRESS MAIL LABEL NO. EV 318 174 036 US
Today's Date: AUGUST 7, 2003

RECEIVED
AUG 19 2003
CARDINAL LAW GROUP

22240 U.S. PTO
10/635963
08/07/03

Dkt. No. CE11234JI023 (9640/133)
Inventor STEPHEN O. BOZZONE
Serial No.: 10/635,963
Filing Date: AUGUST 7, 2003

EXHIBIT A

Express Mail Label No. EV 318 174 036 US

Date of Mailing: August 7, 2003

PATENT
Case No. **CE11234JI023**
(9640/133)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S): STEPHEN O. BOZZONE

TITLE: WIRELESS PERSONAL TRACKING AND
NAVIGATION SYSTEM

ATTORNEYS: MOTOROLA, INC.
INTELLECTUAL PROPERTY - DOCKETING
1303 E. ALGONQUIN ROAD
IL01 - 3RD FLOOR
SCHAUMBURG, IL 60196
(847) 538-2450

Dkt. No. CE11234JI023 (9640/133)
Inventor STEPHEN O. BOZZONE
Serial No.: 10/635,963
Filing Date: AUGUST 7, 2003

EXHIBIT B

WIRELESS PERSONAL TRACKING AND NAVIGATION SYSTEM

5

FIELD OF THE INVENTION

This invention relates generally to personal navigation and tracking systems. More specifically, the invention relates to a personal tracking system comprising a pedometer and an electronic compass electrically coupled to a
10 wireless communication device such as a cell phone or a mobile radio.

BACKGROUND OF THE INVENTION

Position detection systems for motor vehicles and other mobile objects often use global positioning system (GPS) technology to detect the location of an
15 object. In addition, position detectors have been developed recently for detecting the position of the vehicle that augment the GPS readings. For example, some self-contained navigational GPS systems for vehicles have additional integrated speed and directions sensors such as gyroscopes that help detect the direction for a predetermined distance or time and the distance traveled during the period
20 when GPS readings are not valid. Measurements of distance in a detected direction are added cumulatively to the starting-point position measurement to determine the current position.

Portable position detectors based on GPS need to receive GPS timing and signaling information from more than one GPS satellite in order to calculate
25 the location where the receiver is located. Unfortunately, it is common for manmade structures such as buildings and natural structures such as mountains and dense woods to block GPS satellite signals from a portable detector. GPS detectors are often ineffective indoors.

Current portable navigational tracking systems can be successful in an open field or similar environments. Researchers have developed portable position-detection systems that make use of various components including a
5 GPS receiver, magnetic compass, pedometer, accelerometer, gyroscopes, and data from previous terrain readings. For example, Matsuoka and others describe a device with a pedometer, a geomagnetic sensor, and an acceleration sensor to detect the position of a person in "Portable Position Detector and Position
Management System," U.S. Patent 6,546,336 issued April 8, 2003. Readings
10 from the pedometer are used to correlate foot motion to the number of steps taken and the distance traveled.

Expensive and complex systems that have been proposed for personal inertial navigation systems (PINS) use multiple axis accelerometers and gyroscopes to determine the motion of a body of a person and to compute the
15 location of the body based on acceleration and angular rotation information.

A navigation and position detector for determining and indicating the position of a pedestrian might also include a computer memory, an input device, and a display device as described in "Golf Navigation Appliance," Talkenberg et al., U.S. Patent Application 2002/0038178 published March 28, 2002. The
20 method for determining the position of the walker with this navigation appliance includes measuring acceleration values using a motion sensor arranged on a pedestrian; storing in a memory device the measured acceleration values over a time period; and calculating the walking speed and/or distance walked for the user using an estimation model.

25

Besides devices that determine the longitudinal/latitudinal position of a person, there are other products have been developed to give feedback to walkers and runners on their speed, distance, calorie burn and heart rate. For example, a monitor that wraps around the chest measures the heart rate while an accelerometer that clips to a shoelace measures each stride. The collected speed, distance and heart-rate data are sent via a wireless link to the display of a wristwatch-like computer device. The performance data can be uploaded to the Internet for real-time monitoring and logging through a wired connection with a personal computer or a wireless connection with a mobile phone. Ohlenbush and others disclose a system and associated methods that use at least one sensor to detect and measure the stride of a walker or runner in "Monitoring Activity of a User in Locomotion on Foot," U.S. Patent 6,493,652 issued December 10, 2002.

There are a number of beneficial applications for personal inertial navigation and tracking systems. For example, an on-foot personal inertial navigation system can benefit the person with the device directly by providing navigational information in, for example, a heavily forested or deep valley area. Applications for personal inertial tracking systems include the remote monitoring of people such as prisoners, workers in higher-risk work areas, and patients who are prone to wander and get lost.

Personal navigation and tracking systems need to be small, lightweight, low powered, and accurate in environmental conditions where GPS signals cannot be received. The systems should have options for navigational aid to be generated locally and provided to the user or to others for remote tracking of the user. A more desirable system would have a communication link from which an external system or others remote from the wearer could know immediately the movements of the wearer. What is desired therefore, is an inexpensive system and method for tracking and providing navigational aid to individuals, augmenting a global positioning system when needed, thereby overcoming the deficiencies and obstacles of other systems described above.

SUMMARY OF THE INVENTION

One aspect of the invention provides a personal tracking system including a wireless communication device, a pedometer electrically coupled to the
5 wireless communication device, and an electronic compass operably positioned with respect to the pedometer. The wireless communication device receives readings from the pedometer and the electronic compass to provide position information.

Another aspect of the invention is a method of tracking a location of a
10 person. The method comprises the steps of receiving pedometer data from a pedometer, receiving heading information from an electronic compass, determining the location of the person based on the pedometer data and the heading information, and sending a position information message block from a wireless communication device. The position information message block
15 comprises the determined location.

Another aspect of the invention is a system for tracking a location of a person, comprising means for receiving pedometer data, means for receiving heading information, means for determining the location of the person based on the pedometer data and the heading information, and means for sending a
20 position information block with the determined location from a wireless communication device.

Another aspect of the invention is an electronic module for a personal tracking system. The module comprises a controller, a wireless transceiver operably connected between the controller and a pedometer, an electronic
25 compass electrically coupled to the controller, and a wired connection to allow interfacing with a wireless communication device. Position information is determined based on readings from the pedometer and the electronic compass and provided to the wireless communication device via the wired connection.

The present invention is illustrated by the accompanying drawings of various embodiments and the detailed description given below. The drawings should not be taken to limit the invention to the specific embodiments, but are for
5 explanation and understanding. The detailed description and drawings are merely illustrative of the invention rather than limiting, the scope of the invention being defined by the appended claims and equivalents thereof. The foregoing aspects and other attendant advantages of the present invention will become more readily appreciated by the detailed description taken in conjunction with the
10 accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiment of the present invention are illustrated by the accompanying figures, wherein:

15 **FIG. 1** illustrates a personal tracking system, in accordance with one embodiment of the current invention;

FIG. 2 is a block diagram of a system for tracking a location of a person, comprising an electronic module for a personal tracking system, in accordance with one embodiment of the current invention; and

20 **FIG. 3** is a flow diagram of a method for tracking a location of a person, in accordance with one embodiment of the current invention.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

FIG. 1 shows an illustration of a personal tracking system, in accordance with one embodiment of the present invention at **100**. Personal tracking system **110** comprises a wireless communication device **120**, a pedometer **130** electrically coupled to wireless communication device **120**, and an electronic compass **136** operably positioned with respect to pedometer **130**. Readings from pedometer **130** and electronic compass **136** are received by wireless communication device **120** to provide position information. The position information may be used, for example, to determine the location of a person or user **112** inside a building, underground, between tall buildings or in other places where global positioning system (GPS) data is not reliable or not obtainable.

Wireless communication device **120** comprises, for example, a cell phone such as a CDMA, TDMA, GSM or multi-band phone, a mobile radio, an integrated digital enhanced network (iDEN) phone, a wireless network device for a LAN or WLAN, a PDA, or any phone or mobile radio capable of transmitting and receiving packet data. In one example, wireless communication device **120** is a cell phone with a display and an input device for selecting operational modes and viewing results. In another example, wireless communication device **120** is a mobile radio with a display and a walkie-talkie for relatively short-range communication that allows personal tracking and navigation in addition to voice communications. In another example, wireless communication device **120** is an iDEN radio equipped with a GPS unit **140** for determining the location of the radio and user **112** when GPS satellite data is available. Wireless communication device **120** may be, for example, attached to a person's waist, carried in a person's hand, or otherwise coupled to the body of user **112**. Wireless communication device **120** may be connected, for example, by one or more wires to pedometer **130** or wirelessly connected to pedometer **130** with a pair of wireless transceivers **132a** and **132b**.

Pedometer **130**, often attached to the shoe, foot, ankle or leg of user **112**, contains, for example, at least one single-axis accelerometer **134** such as a piezoelectric accelerometer or a silicon-based micromachined accelerometer.

- 5 Accelerometer **134** provides acceleration and deceleration signals corresponding to motion changes of the foot as user **112** ambulates, so that the current position can be determined with respect to a previous position or a reference location by calculating, for example, the number of steps or paces taken and the distance between steps. Pedometer **130** may comprise additional accelerometers **134** to
10 determine, for example, changes in height or deviations from a straight line.

- Pedometer **130** may contain an electronic compass **136** such as a calibrated magnetometer to determine heading information. Electrical signals from electronic compass **136** may be used to ascertain, for example, if user **112** is traveling in a northern direction, southern direction, or any direction in
15 between. Alternatively, electronic compass **136** may be mounted to wireless communication device **120** or to an electronic module **160** within wireless communication device **120**. Electronic compass **136** may be mechanically coupled to wireless communication device **120**, to an electronic module within or connected to wireless communication device **120**, or to pedometer **130**.

- 20 Pedometer **130** may be electrically coupled to wireless communication device **120** via a wired or a wireless link. For example, pedometer **130** may be electrically coupled to wireless communication device **120** in accordance with an IEEE 802.15.4 wireless protocol, a Bluetooth protocol, or other short-range wireless protocol capable of transferring position data between pedometer **130**
25 and wireless communication device **120**. Alternatively, pedometer **130** may be electrically connected to wireless communication device with a wired link such as a serial or parallel data link.

In some cases, elevation or altitude information is desired to aid in determining the location of user **112**. For example, user **112** may walk through a large factory or office building where GPS data is unavailable. As user **112** goes
5 up and down stairs, elevators or escalators, the floor upon which user **112** is located can be determined from altitude information. A barometer **138** provides barometric pressure information from which altitude or height can be determined. Barometric signals are received by wireless communication device **120** to provide altitude information. Barometer **138**, located in pedometer **130**, within
10 electronic module **160**, or within wireless communication device **120**, is electrically coupled to wireless communication device **120** to provide altitude information.

Global positioning system (GPS) unit **140** may be electrically coupled to wireless communication device **120**. GPS signals from GPS unit **140** provide a
15 longitudinal coordinate and a latitudinal coordinate to wireless communication device **120** that can be used to determine position information when GPS satellite signals from GPS satellites **142** are available with sufficient signal strength.

Position information of user **112** may be sent to a server **150** from
20 personal tracking system **110**. Server **150** is in communication with wireless communication device **120** when position information and related command messages are to be transferred. For example, wireless communication device **120** may be connected to server **150** through a cellular antenna system **122**, a cellular phone network **124**, and a combination of wired and wireless networks
25 **126**. Position information is sent from wireless communication device **120** to server **150** in response to a position request. The position request may be generated, for example, from an application running on server **150** or within wireless communication device **120**. The position request may be generated, for example, automatically within a prescribed time limit, semi-automatically when
30 GPS data is no longer available or a GPS signal diminishes below a signal threshold, or manually when prompted by user **112**.

Position information may be generated and displayed locally on wireless communication device **120**. Alternatively, position information may be generated and displayed on a display **152** connected to a computer **154** such as a laptop or personal computer for logging or otherwise tracking user **112**. Position or location information may be stored as desired in a memory **156** connected to server **150**.

FIG. 2 shows a block diagram of a system for tracking a location of a person, in accordance with one embodiment of the present invention at **200**. Location-tracking system **200** comprises a wireless communication device **220** such as a cell phone or a mobile radio and a pedometer **230**, sometimes referred to as a foot pod.

In one embodiment, location-tracking system **200** comprises an electronic module **260** for a personal tracking system. Electronic module **260** comprises a controller **264** and a wireless transceiver **232a** electrically connectable to a matching wireless transceiver **232b** within pedometer **230**. Wireless transceiver **232a** in electronic module **260** may be operably connected to pedometer **230** via wireless transceiver **232b** in pedometer **230** in accordance with an IEEE 802.15.4 wireless protocol, IEEE 802.11 wireless protocol, or other short-range wireless communication protocols. Electronic module **260** may be located within wireless communication device **220** or as an accessory module connectable to wireless communication device **220**. In another embodiment, pedometer **230** is connected by a wired link to electronic module **260**.

Electronic module **260** provides position information to wireless communication device **220**. Electronic module **260** may comprise a wired connection to allow interfacing with wireless communication device **220**. Position information is provided to wireless communication device **220** via the wired connection. Position information from electronic module **260** may be sent to wireless communication device **220** via a wired connection from within wireless communication device **220** or via a wired connection such as a serial port **262**,

which is external to wireless communication device **220**. Serial port **262** may be located in electronic module **260** with a matching port located in wireless communication device **220** for sending and receiving data, messages, and
5 position information.

Pedometer **230** comprises at least one accelerometer **234** for detecting one or more steps of a user and the distance between the steps. Pedometer **230** may comprise an electronic compass **236**, such as a magnetometer, to provide heading information. Pedometer data received from pedometer **230** and heading
10 information from electronic compass **236** are used to determine the position or location of the person or user. Electronic compass **236** may be electrically coupled to controller **264** via a wired or a wireless link.

Location-tracking system **200** may receive altitude information from a barometer **238** to determine the location of the person or user based on the
15 altitude information. Barometer **238** may be comprised within pedometer **230**. In one example, a controller **228** within pedometer **230** runs microcode to extract signals from accelerometer **234**, electronic compass **236** and barometer **238**, and to execute commands for transmitting position information to electronic module **260** or to wireless communication device **220**. Controller **228** may calculate
20 position information directly, or alternatively, send signal information to a controller either within electronic module **260** or wireless communication device **220** where the position or location information can be calculated. Alternatively, position or location information may be computed at an external server or a digital computing device connected to wireless communication device **220**.
25 Position information or signals from accelerometer **234**, electronic compass **236**, or barometer **238** within pedometer **230** may be stored in a memory **244** that is electrically coupled to controller **228**, and may be extracted or inspected when desired.

For example, microcode running on controller **264** within electronic module **260** calculates the position of a user with respect to a reference or starting location based on the number of steps, distance between steps, and the direction of the steps. Starting or reference information may be provided, for example, from a GPS unit **240** located within wireless communication device **220** or from GPS unit **240** within electronic module **260**. Alternatively, starting or reference information may be provided by voice or keypad input in response to an application running on wireless communication device **220**.

10 In an alternative embodiment, electronic module **260** contains an electronic compass **266** from which heading information is obtained. Electronic compass **266** may be electrically coupled to controller **264** via a wired link. Pedometer data received from pedometer **230** and heading information from electronic compass **266** are used to determine the location of the person or user.

15 In another embodiment, electronic module **260** contains a barometer **268** electrically coupled to controller **264** from which altitude information is obtained. Altitude information is determined based on barometric signals from barometer **268**. Location-tracking system **200** receives altitude information from barometer **268** to determine the location of the person or user based on the altitude information.

20 In another embodiment, electronic module **260** comprises GPS unit **240** (not shown). In this embodiment, GPS unit **240** is electrically coupled to controller **264**. GPS signals from GPS unit **240** located in electronic module **260** provide a longitudinal coordinate and a latitudinal coordinate to controller **264**.

25 A computer application may be loaded into and operated locally within wireless communication device **220** or electronic module **260** to track the location of a person or provide navigation services to a user. The application may be initiated automatically or manually at the request of the user. A personal reference location input may be received, for example, from an external server, from an application running locally, or in response to a user input. When the

30

personal reference location input is received, the location of the person may be determined based on that personal reference location input. For example, GPS coordinate information is received from GPS unit **240**, and the location of the person is determined based on the GPS coordinate information. Alternatively, a user can indicate via a voice or key entry his or her current location onto a map or a table displayed by wireless communication device **220**, irregardless of whether or not GPS coordinate information is used.

Updates to the initial personal reference location may be made with additional GPS coordinates from GPS unit **240** or from pedometer **230** when GPS signals are not available. For example, updates for the location of the person may be made automatically or manually with an additional personal reference location input.

A position information message block comprising the determined location may be sent from wireless communication device **220** to, for example, a server or an application running on a portable digital assistant (PDA), laptop or personal computer connected to wireless communication device **220**. The position information message block may be received at a server, and personal tracking information may be updated based on the received position information message block.

FIG. 3 shows a flow diagram of a method for tracking a location of a person, in accordance with one embodiment of the present invention at **300**. Location tracking method **300** comprises various steps to track the position or location of a person.

25

To start, a person may attach a pedometer to a foot, shoe, ankle, or other suitable portion of the body. The pedometer is wired or wirelessly connected to a cell phone or radio. An electronic module with a short-range wireless link to the pedometer may be connected to the cell phone or radio as an accessory using, for example, a serial port in the cell phone or radio. The electronic module, cell phone, or radio has sufficient hardware and software to receive pedometer data and heading information from an electronic compass to determine the location of the person.

10 A personal reference location input is received, as seen at block 305. The personal reference location input may be received, for example, from an application running on a wireless communication device, from an application running on a remotely connected server, or from a manual input by a user of the system. The location of the person is then determined based on the personal
15 reference location input. For example, a GPS unit coupled to the wireless communication device may be used to provide GPS coordinate information. After GPS coordinate information is received, the location of the person is determined based on the GPS coordinate information. In another example, a map of a building where the user is currently located may be displayed on the
20 wireless communication device, and the user indicates his or her current location with a personal reference location input. The location of the person may be determined continuously when GPS coordinate information is readily available.

 In situations where GPS coordinate information is not available or not reliable due to, for example, low signal strengths from the GPS satellites or the
25 inability to obtain an accurate signal from within urban canyons, GPS coordinate information or other user-provided position or location information may be updated with local tracking information from a pedometer and an electronic compass that are coupled to the user. When a user enters a building or walks extensively within a facility that has limited GPS reception, for example,
30 pedometer and heading information may be used to determine the location of the

user, verifying, adjusting or augmenting previous position or location information from a GPS reading or other personal reference location input. At this point, the GPS unit may be powered down and the personal tracking system powered up to
5 extend battery life.

Pedometer data may be received from a pedometer coupled to the user, as seen at block **310**. Pedometer data may comprise, for example, the number of steps taken and the distance between steps. Heading information indicating the geographical direction in which the steps are taken may be received from an
10 electronic compass such as a calibrated magnetometer. The electronic compass may be located, for example, within the pedometer, within an electronic module attachable to a wireless communication device, or within the wireless communication device. The location of the person may be determined based on the pedometer data from the pedometer and the heading information data from
15 the electronic compass. For example, the location of the user is calculated by an algorithm that takes the initial GPS coordinate information and adds the distance corresponding to the number of steps in a geographical direction indicated by the electronic compass heading information. As the user changes location, the position information may be updated. Updates from pedometer data and
20 heading information may be made until, for example, a new personal reference location input is received or valid GPS data becomes available, as seen at block **305**.

In cases where a person is indoors and it is desirable to know, for example, the floor where the person is, a barometer may be used to determine
25 the altitude. Altitude information is received from the barometer, as seen at block **315**. The barometer may be located, for example, within the pedometer, within an electronic module attachable to a wireless communication device, or within the wireless communication device. The location of the person may be determined based on the altitude information or in combination with other
30 position information from the pedometer or from the GPS unit. After altitude

information is received, additional GPS data may be received, as seen at block 305, or additional pedometer data may be received, as sent at block 310, and then position information is determined and updated.

5 The personal tracking system may be used for personal navigation or for other applications such as tracking by a remote party. In a personal navigation mode, the user sees the location data on the screen or display of the wireless communication device or other digital computing device such as a PDA or a laptop connected to the wireless communication device to aid the user in
10 navigation. In the tracking mode, position or location information may be sent to a server for another party to track the person's location.

 When the position information has been determined, a position information message block may be sent from the wireless communication device, as seen at block 320. The position information message block comprises, for example,
15 header information and a message body with one or more fields or entries containing the position information or the determined location. The position information message block may be sent, for example, from a cell phone, a mobile radio, an iDEN phone, or any phone or mobile radio capable of transmitting and receiving packet data. The transmission of the position information message
20 block may be sent, for example, via an iDEN, CDMA, TDMA or GSM phone, or via a wireless LAN (WLAN) operating according to an 802.11b or other suitable wireless protocol.

 The position information message block may be received at a server, as seen at block 325. The server may be located, for example, at a central location
25 or at the user's home or office. Alternatively, the position information message block may be forwarded to a user's personal computer, personal digital assistant, or other digital device in proximity to the user or at a remote location with respect to the user. The position information may be stored at a desired location for later downloading or processing. Personal tracking information based on the received
30 position information message block may be updated.

The process may be continued as desired, as seen at block **330**. When available, position or location information may be determined from new GPS coordinates or from new pedometer data as seen at block **305** or at block **310**.

- 5 Position information may be updated when changes in altitude are detected, as seen at block **315**.

While the embodiments of the invention disclosed herein are presently preferred, various changes and modifications can be made without departing from the spirit and scope of the invention. The scope of the invention is indicated
10 in the appended claims, and all changes that come within the meaning and range of equivalents are intended to be embraced therein.

CLAIMS

What is claimed is:

5

1. A personal tracking system, comprising:
a wireless communication device;
a pedometer electrically coupled to the wireless communication
device; and

10

an electronic compass operably positioned with respect to the pedometer, wherein readings from the pedometer and the electronic compass are received by the wireless communication device to provide position information.

15

2. The system of claim 1 wherein the wireless communication device comprises one of a cell phone or a mobile radio.

3. The system of claim 1 wherein the pedometer is electrically coupled to the wireless communication device via a wired or wireless link.

20

4. The system of claim 1 wherein the pedometer is electrically coupled to the wireless communication device in accordance with a protocol selected from the group consisting of: an IEEE 802.15.4 wireless protocol, and IEEE 802.11 wireless protocol, and a short-range wireless communication protocol.

25

5. The system of claim 1 wherein the pedometer comprises at least one single-axis accelerometer.

6. The system of claim 1 wherein the electronic compass is
mechanically coupled to one of the wireless communication device or the pedometer.

30

7. The system of claim 1 further comprising:
a barometer electrically coupled to the wireless communication
device, wherein barometric signals are received by the wireless communication
5 device to provide altitude information.

8. The system of claim 1 further comprising:
a GPS unit electrically coupled to the wireless communication
device, wherein GPS signals from the GPS unit provide a longitudinal coordinate
10 and a latitudinal coordinate to the wireless communication device.

9. The system of claim 1 further comprising:
a server in communication with the wireless communication device,
wherein position information is sent from the wireless communication device to
15 the server in response to a position request.

10. A method of tracking a location of a person, comprising:
receiving pedometer data from a pedometer;
receiving heading information from an electronic compass;
20 determining the location of the person based on the pedometer
data and the heading information; and
sending a position information message block from a wireless
communication device, the position information message block comprising the
determined location.

25

11. The method of claim 10 wherein the position information message
block is sent from one of a cell phone or a mobile radio.

12. The method of claim 10 further comprising:
receiving altitude information from a barometer; and
determining the location of the person based on the altitude
5 information.
13. The method of claim 10 further comprising:
receiving a personal reference location input; and
determining the location of the person based on the personal
10 reference location input.
14. The method of claim 10 further comprising:
receiving GPS coordinate information; and
determining the location of the person based on the GPS
15 coordinate information.
15. The method of claim 10 further comprising:
receiving the position information message block at a server; and
updating personal tracking information based on the received
20 position information message block.
16. A system for tracking a location of a person, comprising:
means for receiving pedometer data from a pedometer;
means for receiving heading information from an electronic
25 compass;
means for determining the location of the person based on the
pedometer data and the heading information; and
means for sending a position information message block from a
wireless communication device, the position information message block
30 comprising the determined location.

17. The system of claim 16 further comprising:
means for receiving altitude information from a barometer; and
means for determining the location of the person based on the
5 altitude information.

18. The system of claim 16 further comprising:
means for receiving a personal reference location input; and
means for determining the location of the person based on the
10 personal reference location input.

19. The system of claim 16 further comprising:
means for receiving GPS coordinate information; and
means for determining the location of the person based on the GPS
15 coordinate information.

20. The system of claim 16 further comprising:
means for receiving the position information message block at a
server; and
20 means for updating personal tracking information based on the
received position information message block.

21. An electronic module for a personal tracking system, comprising:
a controller;
a wireless transceiver operably connected between the controller
5 and a pedometer;
an electronic compass electrically coupled to the controller; and
a wired connection to allow interfacing with a wireless
communication device, wherein position information is determined based on
readings from the pedometer and the electronic compass, and wherein position
10 information is provided to the wireless communication device via the wired
connection.
22. The module of claim 21 wherein the electronic compass is
electrically coupled to the controller via one of a wired or a wireless link.
15
23. The module of claim 21 wherein the wireless communication device
comprises one of a cell phone or a mobile radio.
24. The module of claim 21 wherein the wireless transceiver is
20 operably connected to the pedometer in accordance with an IEEE 802.15.4
wireless protocol.
25. The module of claim 21 further comprising:
a barometer electrically connected to the controller, wherein altitude
25 information is determined based on barometric signals from the barometer.
26. The module of claim 21 further comprising:
a GPS unit electrically coupled to the controller, wherein GPS
signals from the GPS unit provide a longitudinal coordinate and a latitudinal
30 coordinate to the controller.

ABSTRACT OF THE DISCLOSURE

The invention provides a personal tracking system comprising a wireless communication device, a pedometer electrically coupled to the wireless
5 communication device, and an electronic compass operably positioned with respect to the pedometer. The wireless communication device receives readings from the pedometer and the electronic compass to provide position information. A method of tracking a location of a person, a system for tracking the location of a person, and an electronic module for a personal tracking system are also
10 disclosed.

FIG. 1




FIG. 2





FIG. 3



ABSTRACT OF THE DISCLOSURE

The invention provides a personal tracking system comprising a wireless communication device, a pedometer electrically coupled to the wireless
5 communication device, and an electronic compass operably positioned with respect to the pedometer. The wireless communication device receives readings from the pedometer and the electronic compass to provide position information. A method of tracking a location of a person, a system for tracking the location of a person, and an electronic module for a personal tracking system are also
10 disclosed.

Dkt. No. CE11234JI023 (9640/133)
Inventor STEPHEN O. BOZZONE
Serial No.: 10/635,963
Filing Date: AUGUST 7, 2003

EXHIBIT C